



118

THREAD GARD

Heavy-Duty Thread Protection and Wire Rope Coating & Corrosion Inhibitor

- GEAR OILS
- MOTOR OILS
- HYDRAULIC OILS
- PIPE COATINGS
- THREAD SEALANTS
- BEARING GREASES
- SPECIALTY GREASES
- THREAD COMPOUNDS
- SUCKER ROD COATINGS
- OUTSIDE PRESERVATIVES
- WIRELINE GREASE SEALS
- CLEANERS & DEGREASERS
- PIPE STORAGE COMPOUNDS
- RUST & CORROSION INHIBITORS
- THREAD LOCKING COMPOUNDS
- VALVE LUBRICANTS & SEALANTS
- TOOL JOINT & DRILL COLLAR COMPOUNDS

PRODUCT DESCRIPTION

118 Thread Gard is an extra heavy duty corrosion and rust preventative. Its waxy, non-tacky, pliable film provides both indoor and outdoor protection to threads against the damaging effects of rust, salt spray corrosion, H₂S, contamination, moisture, and downhole chemicals.

BENEFITS

- Corrosion and rust preventive
- Easy removal of protective film
- Provides indoor and outdoor protection
- Protects against H₂S and downhole chemicals

APPLICATION

118 Thread Gard is especially recommended for protection of threads where easy removal of the protective film is desirable.

118 Thread Gard is used on wire rope as a lubricant and for protection against H₂S and downhole chemicals such as calcium chloride.

118 Thread Gard may be applied by brushing or spraying.

TYPICAL OBSERVATIONS

Color	Brown
Odor	Mild Solvent
Density, lb/gal @ 77°F (25°C)	7.44
Specific Gravity, @ 77°F (25 °C)	0.892
Flash Point, ASTM D-56	145°F (62°C)
Viscosity, ASTM D-1200	
#4 Ford cup @ 77°F (25°F)	55 sec
Solubility in Water	Insoluble
Boiling Point	300°F (149°C)
Shelf Life (unopened container)	One year

RELATED PRODUCTS

- MP-56 Metal Parts Protector
- 125 Pipe Storage Compound
- 127 Pipe Storage Compound
- 130 Water Displacer and Corrosion Inhibitor

