



156

MP GREASE

With Moly and Graphite

- GEAR OILS
- MOTOR OILS
- HYDRAULIC OILS
- PIPE COATINGS
- THREAD SEALANTS
- BEARING GREASES
- SPECIALTY GREASES
- THREAD COMPOUNDS
- SUCKER ROD COATINGS
- OUTSIDE PRESERVATIVES
- WIRELINE GREASE SEALS
- CLEANERS & DEGREASERS
- PIPE STORAGE COMPOUNDS
- RUST & CORROSION INHIBITORS
- THREAD LOCKING COMPOUNDS
- VALVE LUBRICANTS & SEALANTS
- TOOL JOINT & DRILL COLLAR COMPOUNDS

PRODUCT DESCRIPTION

Liquid-O-Ring 156 is a high temperature machinery lubricant formulated with moly for added lubricity. *Liquid-O-Ring* 156 replaces many specialty products in applications where conventional multipurpose lubricants fail. It is designed specifically for heavy load applications under low speeds as well as applications with high loads, high vibrations, and shock loads to prevent untimely equipment wear. *Liquid-O-Ring* 156 has good pumpability and excellent water resistance. The extreme properties of *Liquid-O-Ring* 156 are due to its non-emulsifying characteristics which do not allow it to be broken down and eventually washed out. It has higher heat resistance than most greases. The combination of a high dropping point, high EP properties, and inhibitors for rust and oxidation of *Liquid-O-Ring* 156 assures maximum protection against wear and seizure even under the most demanding situations.

TYPICAL OBSERVATIONS

Color	Gray
Texture	Tacky
Thickener	Aluminum Complex
Density, lb/gal @ 77°F (25°C)	7.35
Specific Gravity @ 77°F (25°C)	0.881
Dropping Point, ASTM D-2265	>500°F (260°C)
Flash Point, ASTM D-92	>450°F (232°C)
Penetration, ASTM D-217	
worked @ 77°F (25°C)	295
NLGI Grade	2
Base Oil Viscosity	
cSt @ 40°C	212.5
Corrosion Preventive Properties,	
ASTM D-1743 @ 125°F (51°C)	Pass
Oil Separation, ASTM D-1742	
@ 77°F (25°C)	0.40%
Water Washout, ASTM D-1264 @ 79°C	Nil
Evaporation Loss,	
ASTM D-972 @ 210°F (98°C)	0.44%
Shelf Life (unopened container)	Two years

BENEFITS

- Made with moly for maximum lubricity
- Good pumpability
- Excellent water resistant
- Heat resistant
- High EP properties
- Rust and oxidation inhibitors
- Maximum protection against wear and seizure
- Will not break down
- High shock loads

APPLICATION

Liquid-O-Ring 156 is recommended for use where shock load, high loads, high vibration, contamination, or high temperature is a factor. Applications of *Liquid-O-Ring* 156 include shock absorbers, for wheel bearings with disc brakes, trailer bearings, and in machinery used in farming, construction, automotive, mining, paper, and steel mill industries.



© 2012, BALMAR LLC Made in U.S.A.
WARRANTY Because the conditions of use and the supervision of application are beyond our control, we assume no liability for any product failure or other damage beyond the purchase price of the material furnished by us. No agent, representative, or employee of this Company is authorized to change this provision, which relates to all goods delivered, whether sold, delivered as samples, or otherwise. Each user should independently determine the suitability of this product based on their specific application.

Manufactured by
BALMAR LLC

616 WEST PONT DES MOUTON ROAD | LAFAYETTE, LA 70507

Sales Locations:
 LAFAYETTE, LA | HOUSTON, TX | LONGVIEW, TX | MIDLAND, TX | OKLAHOMA CITY, OK

*Registered trade name of Oil Center Research, Inc. 06/19/19
 The product information and specifications listed in this publication are constantly being updated to keep up with government regulations and technology changes. Please visit our web site, www.oilcenter.com, or contact your Account Representative for the most current information relating to this product.