

189

SPIN EASY

Arctic Valve Seal

PRODUCT DESCRIPTION

189 Spin Easy Valve Sealant is designed for use on gate valves and plug valves in arctic conditions. It can be used at temperatures as low as -25°F (-31°C). 189 Spin Easy is a blend of synthetic oils and other ingredients to provide lubrication and protection to valves under demanding arctic temperature conditions. It is resistant to hydrocarbons, sour gas, fresh or salt water, H₂S and CO₂. 189 Spin Easy contains a proprietary blend of solid ingredients to protect valve gates and seats from damage due to continuous use. 189 Spin Easy can be used as a general-purpose lubricant on various types of equipment under arctic temperatures.

APPLICATION

189 Spin Easy recommended applications include plug valves, gate valves, ball valves, well valves, high pressure valves, valve servicing for water, glycerine, ammonia, gasses, solvents, gasoline, H₂S, crude oil and hydrocarbons. It can also be used as a general-purpose lubricant on various types of equipment under arctic temperatures.

TYPICAL OBSERVATIONS

Color	Gray
Appearance	Smooth Paste
Density, lb/gal @ 77°F (25°C)	9.00
Specific Gravity, @ 77°F (25°C)	1.08
Dropping Point, ASTM D-2265	>500°F (>260°C)
Flash Point, ASTM D-92	>400°F (>204°C)
Penetration, ASTM D-217 worked @ 77°F (25°C)	290
Temperature Range	-25°F to >400°F (-31°C to >204°C)
Shelf Life (unopened container)	Two years

BENEFITS

- Synthetic base
- Arctic grade
- Water resistant
- H₂S and CO₂ resistant
- Resists galling
- Protective film
- Resistant to HCL

FRAC

FLUSH

ARCTIC

STORAGE

SEALANTS

CLEANERS

ASSEMBLY

BALL VALVE
LUBRICANTS

GATE VALVE
LUBRICANTS

PLUG VALVE
LUBRICANTS

STICK PACKING



Liquid-O-Ring[®]*

© 2012, BALMAR LLC
WARRANTY Because the conditions of use and the supervision of application are beyond our control, we assume no liability for any product failure or other damage beyond the purchase price of the material furnished by us. No agent, representative, or employee of this Company is authorized to change this provision, which relates to all goods delivered, whether sold, delivered as samples, or otherwise. Each user should independently determine the suitability of this product based on their specific application.

*Registered Tradename of Oil Center Research, Inc.

Manufactured by
BALMAR LLC

616 WEST PONT DES MOUTON ROAD | LAFAYETTE, LA 70507

Sales Locations:
LAFAYETTE, LA | HOUSTON, TX | LONGVIEW, TX | MIDLAND, TX | OKLAHOMA CITY, OK

Made in U.S.A. 03/31/17

The product information and specifications listed in this publication are constantly being updated to keep up with government regulations and technology changes. Please visit our website, www.oilcenter.com, or contact your Account Representative for the most current information relating to this product.