



Liquid-O-Ring®*

YOUR SUPER CENTER FOR OVER 1,000 TOP PERFORMANCE PRODUCTS SERVING INDUSTRIES WORLDWIDE

WWW.OILCENTER.COM

270 HONEY SEAL

Pressure Control Wireline Grease—Corrosion and H₂S Inhibited

PRODUCT DESCRIPTION

270 Honey Seal is a pressure control grease developed for wireline operations. 270 Honey Seal contains a corrosion inhibitor package to provide protection to braided lines exposed to downhole chemicals, brines, acid, and hydrogen sulfide. 270 Honey Seal was developed with today's wireline market in mind and is manufactured in the tradition of *Liquid-O-Ring* wireline grease seal to meet the most demanding standards.

Liquid-O-Ring Wireline Grease Seal is the standard of the wireline industry and 270 Honey Seal follows in the tradition of quality performance under demanding conditions. 270 Honey Seal will perform up to standards for most wireline pressure operations. If you are looking for the best you can depend on *Liquid-O-Ring*.

BENEFITS

- *Liquid-O-Ring* quality and performance
- Corrosion inhibitor package
- Protects against H₂S
- Available in the popular grades

APPLICATION

270 Honey Seal Pressure Control Grease is recommended for braided wireline, cables, and wire rope. Apply 270 Honey Seal using grease injector control heads and cable lubricators.

TYPICAL OBSERVATIONS

Color	Amber
Texture	Tacky Liquid
Odor	Mild
Density Range, lb/gal @ 77°F (25°C)	7.00–7.50
Specific Gravity Range @ 77°F (25°C)	0.839–0.899
Flash Point, ASTM D-92	390°F (198°C)
Rust Preventive Test,	
ASTM D-3603 @ 140°F (60°C)	Pass
Viscosity, kinematic @ 40°C, cSt	10,500 - 11,500
Viscosity Index (VI)	315
Shelf Life (unopened container)	Four years

RELATED PRODUCTS

In addition to 270 Honey Oil, a complete line of wireline grease seal products and line sprays is available. Products for use in severe CO₂ service, biodegradable products, and arctic grade products are also available. There are no wireline products currently on the market which approach the quality, versatility and proven performance record of *Liquid-O-Ring*, the industry standard.

- 765** Low Temp. Wireline Grease Seal (H₂S Inhibitor)
- 780** Biodegradable Wireline Grease Seal

- GEAR OILS
- MOTOR OILS
- HYDRAULIC OILS
- PIPE COATINGS
- THREAD SEALANTS
- BEARING GREASES
- SPECIALTY GREASES
- THREAD COMPOUNDS
- SUCKER ROD COATINGS
- OUTSIDE PRESERVATIVES
- WIRELINE GREASE SEALS
- CLEANERS & DEGREASERS
- PIPE STORAGE COMPOUNDS
- RUST & CORROSION INHIBITORS
- THREAD LOCKING COMPOUNDS
- VALVE LUBRICANTS & SEALANTS
- TOOL JOINT & DRILL COLLAR COMPOUNDS



© 2021, BALMAR LLC Made in U.S.A.

WARRANTY Because the conditions of use and the supervision of application are beyond our control, we assume no liability for any product failure or other damage beyond the purchase price of the material furnished by us. No agent, representative, or employee of this Company is authorized to change this provision, which relates to all goods delivered, whether sold, delivered as samples, or otherwise. Each user should independently determine the suitability of this product based on their specific application.

Manufactured by

BALMAR LLC

616 WEST PONT DES MOUTON ROAD | LAFAYETTE, LA 70507

Sales Locations:

LAFAYETTE, LA | HOUSTON, TX | LONGVIEW, TX | MIDLAND, TX | OKLAHOMA CITY, OK

*Registered trade name of Oil Center Research, Inc.

The product information and specifications listed in this publication are constantly being updated to keep up with government regulations and technology changes. Please visit our web site, www.oilcenter.com, or contact your Account Representative for the most current information relating to this product.