



# 282 CHUCK GREASE

- GEAR OILS
- MOTOR OILS
- HYDRAULIC OILS
- PIPE COATINGS
- THREAD SEALANTS
- BEARING GREASES
- SPECIALTY GREASES
- THREAD COMPOUNDS
- SUCKER ROD COATINGS
- OUTSIDE PRESERVATIVES
- WIRELINE GREASE SEALS
- CLEANERS & DEGREASERS
- PIPE STORAGE COMPOUNDS
- RUST & CORROSION INHIBITORS
- THREAD LOCKING COMPOUNDS
- VALVE LUBRICANTS & SEALANTS
- TOOL JOINT & DRILL COLLAR COMPOUNDS

## PRODUCT DESCRIPTION

282 Chuck Grease is a heavy-duty lubricant manufactured to reduce seizing, galling, and wear of power chucks. Designed to increase the clamping ability of power chucks, 282 Chuck Grease withstands high pressure and has a high resistance to centrifugal force. 282 Chuck Grease lowers maintenance cost while extending the life of chucks.

## BENEFITS

- Heavy-duty applications
- Reduces seizing, galling, friction, and wear
- Increases clamping ability
- Withstands high pressure
- High resistance to centrifugal force

## APPLICATION

282 Chuck Grease may be applied to power chucks to extend the life of the chuck. Areas of 282 Chuck Grease applications include power chucks and standard chucks plus press fits, wear-in, and guides and ways. 282 Chuck Grease may also be used on fasteners as an anti-seize lubricant when assembling the chuck.

## TYPICAL OBSERVATIONS

Appearance	Paste
Color	Tan
Odor	Mild Petroleum
Density, lb/gal	8.50
Specific Gravity	1.019
Penetration,	
ASTM D-217 @ 77°F (25°C)	235
Oil Separation,	
ASTM D-1742 @ 77°F (25°C)	Nil
Dropping Point, ASTM D-2265	330°F (165°C)
Flash Point, ASTM D-92	>400°F (204°C)
Evaporation Loss,	
ASTM D-972 @ 210°F (98°C)	0.75%
Water Washout Characteristics,	
ASTM D-1264 @ 100°F (37°C)	2.5%
Shelf Life (unopened container)	Two years

