



# 570

## SUPER BLUE MAX Cleaner and Degreaser

- GEAR OILS
- MOTOR OILS
- HYDRAULIC OILS
- PIPE COATINGS
- THREAD SEALANTS
- BEARING GREASES
- SPECIALTY GREASES
- THREAD COMPOUNDS
- SUCKER ROD COATINGS
- OUTSIDE PRESERVATIVES
- WIRELINE GREASE SEALS
- CLEANERS & DEGREASERS
- PIPE STORAGE COMPOUNDS
- RUST & CORROSION INHIBITORS
- THREAD LOCKING COMPOUNDS
- VALVE LUBRICANTS & SEALANTS
- TOOL JOINT & DRILL COLLAR COMPOUNDS

### PRODUCT DESCRIPTION

570 Super Blue Max is an excellent heavy-duty cleaner and degreaser, specially designed for industrial use. A non-hazardous, water-based product 570 Super Blue Max penetrates and dissolves the buildup of grease, oil, wax, and soil without harming the environment. 570 Super Blue Max is non-corrosive to metals, safe on fabrics, and will not dull painted surfaces.

### BENEFITS

- Environmentally safe
- Heavy-duty
- Non-flammable
- Non-hazardous
- Non-toxic
- Non-caustic
- Non-combustible
- Dissolves grease and oil
- Safe on fabrics
- Will not dull painted surfaces

### APPLICATION

570 Super Blue Max is a versatile product for degreasing and cleaning auto and industrial engines, oil rigs, vinyl, plastic, machinery, equipment, and whitewall tires. 570 Super Blue Max industry applications include automotive, industrial, marine, aviation, metal fabrication, and electronics.

570 Super Blue Max may be used for pressure washing, steam cleaning, brushing, or spraying.

Dilutions vary depending on type of soil to be removed and type of equipment being used.

- For difficult jobs: 1 pt (473 ML) 570 Super Blue Max per gallon (4 L) of water
- For heavy-duty jobs: 8 oz (.24 L) 570 Super Blue Max per gallon (4 L) of water
- For medium-duty job: 4 oz (.12 L) 570 Super Blue Max per gallon (4 L) of water
- For light-duty jobs: 2 oz (.10 L) 570 Super Blue Max per gallon (4 L) of water

### TYPICAL OBSERVATIONS

Color	Blue
Appearance	Liquid
Odor	Mild
pH	12.75
Density lb/gal @ 77°F (25°C)	8.70
Specific Gravity @ 77°F (25°C)	1.043
Vapor Pressure @ 20°C	<0.04
Boiling Point	212°F (100°C)
Flash Point	None
Freezing Point	28°F (-2°C)
Auto Ignition	None to 500°F (260°C)
Evaporation Rate	>1
Solubility in water	Complete
Shelf Life (unopened container)	Two years

### RELATED PRODUCTS

- 557 Blue Sparkle Liquid Rig Wash and Bilge Cleaning Compound
- 573 Rig Washing Compound
- 576 Rig Wash
- 9075 Super Blue Max Cleaner and Degreaser
- 9561 Rig Washing Compound
- 9562 Rig Wash
- 9676B Sparkle Liquid Rig Wash and Bilge Cleaning Compound
- 9692 Rig Sparkle

