



# 605

## TUBULAR HANGER SEALANT

### Extreme High Temperature Valve Lubricant and Sealant

- GEAR OILS
- MOTOR OILS
- HYDRAULIC OILS
- PIPE COATINGS
- THREAD SEALANTS
- BEARING GREASES
- SPECIALTY GREASES
- THREAD COMPOUNDS
- SUCKER ROD COATINGS
- OUTSIDE PRESERVATIVES
- WIRELINE GREASE SEALS
- CLEANERS & DEGREASERS
- PIPE STORAGE COMPOUNDS
- RUST & CORROSION INHIBITORS
- THREAD LOCKING COMPOUNDS
- VALVE LUBRICANTS & SEALANTS
- TOOL JOINT & DRILL COLLAR COMPOUNDS

#### PRODUCT DESCRIPTION

605 Tubular Hanger Sealant is a valve lubricant and sealant with moly for high temperature application. 605 Tubular Hanger Sealant exhibits excellent resistance to washout from oils, hydrocarbons, asphalts, and water. Corrosion inhibitors and extreme pressure additives in 605 Tubular Hanger Sealant provide for extended service life and compatibility under harsh conditions.

#### BENEFITS

- Rust, corrosion, and oxidation preventive
- Non-melting
- Provides tighter seal
- Excellent washout resistance
- Extreme pressure additives
- Extends service life

#### APPLICATION

Apply 605 Tubular Hanger Sealant using a packing gun, hand or air-operated lubricator.

Recommended applications of 605 Tubular Hanger Sealant include plug valves, high pressure valves, gate valves, valves in high temperature service, ball valves, asphalts, wellheads, valves servicing hot oils, and hydrocarbons.

#### TYPICAL OBSERVATIONS

Form	"K" sticks
Color	Black
Odor	None
Active Component	LIIQUILON®
Manufacturing Process	Fluoromation
Penetration, Stick	
ASTM D-217	100
Density, lb/gal @ 77°F (25°C)	8.70
Specific Gravity	1.04
Corrosion Preventive Test	
ASTM 1743 @ 125°F (51°C)	Pass
Oil Separation,	
ASTM 1742 @ 77°F (25°C)	Nil
Water Resistant	Yes
Service Temperature	400°F (204°C)
Service Pressure	10,000 psi
Solubility	Water Insoluble
Shelf Life (unopened container)	Two years
Other Properties	Residual Lubrication Excellent Sealing Non-corrosive

