



Liquid-O-Ring®*

YOUR SUPER CENTER FOR OVER 1,000 TOP PERFORMANCE PRODUCTS SERVING INDUSTRIES WORLDWIDE

WWW.OILCENTER.COM

760ML

OPEN GEAR LUBE

With Moly and LIQUILON®*

- GEAR OILS
- MOTOR OILS
- HYDRAULIC OILS
- PIPE COATINGS
- THREAD SEALANTS
- BEARING GREASES
- SPECIALTY GREASES
- THREAD COMPOUNDS
- SUCKER ROD COATINGS
- OUTSIDE PRESERVATIVES
- WIRELINE GREASE SEALS
- CLEANERS & DEGREASERS
- PIPE STORAGE COMPOUNDS
- RUST & CORROSION INHIBITORS
- THREAD LOCKING COMPOUNDS
- VALVE LUBRICANTS & SEALANTS
- TOOL JOINT & DRILL COLLAR COMPOUNDS

PRODUCT DESCRIPTION

760ML is an excellent solid-film lubricant that is specially formulated with molybdenum disulfide and LIQUILON®*. 760ML reduces friction and wear by forming a tough, continuous lubricating film on the gear surface. 760ML dampens gear noise and withstands gear and cable pressure, preventing costly corrosion. Due to its adhesive nature, 760ML will not drip, wash off or shear off.

BENEFITS

- Contains Moly and LIQUILON®*
- Reduces friction and wear
- Dampens gear noise
- Contains corrosion inhibitors
- Will not drip, wash off or shear off
- Economical

APPLICATION

760ML may be applied by swab, brush and automatic or manual applicator.

TYPICAL OBSERVATIONS

Color	Black
Texture	Smooth
Active Ingredient	LIQUILON®
Manufacturing Process	Fluoromation
Density, lb/gal @ 77°F (25°C)	8.10
Specific gravity @ 77°F (25°C)	0.97
Dropping Point, ASTM D-2265	>500°F (>260°C)
Flash Point, ASTM D-92	>400°F (204°C)
Penetration ASTM D-217	
worked @ 77°F (25°C)	305
Shelf Life (unopened container)	Two Years

RELATED PRODUCTS

760 Open Gear Lubricant with Moly



© 2012, BALMAR LLC Made in U.S.A.

WARRANTY Because the conditions of use and the supervision of application are beyond our control, we assume no liability for any product failure or other damage beyond the purchase price of the material furnished by us. No agent, representative, or employee of this Company is authorized to change this provision, which relates to all goods delivered, whether sold, delivered as samples, or otherwise. Each user should independently determine the suitability of this product based on their specific application.

Manufactured by

BALMAR LLC

616 WEST PONT DES MOUTON ROAD | LAFAYETTE, LA 70507

Sales Locations:

LAFAYETTE, LA | HOUSTON, TX | LONGVIEW, TX | MIDLAND, TX | OKLAHOMA CITY, OK

*Registered trade name of Oil Center Research, Inc. 08/28/14

The product information and specifications listed in this publication are constantly being updated to keep up with government regulations and technology changes. Please visit our web site, www.oilcenter.com, or contact your Account Representative for the most current information relating to this product.