

INDUSTRIAL LUBRICATING COMPOUNDS

OIL CENTER RESEARCH INTERNATIONAL, L.L.C.



Oil Center Research was founded in 1958 from a vision of two individuals with only one product to sell. Over the past 50 years, Oil Center Research International, L.L.C.'s product line has grown to include over 1,000 products that are sold in more than 80 countries. The Company motto, "Seal of Dependability," signifies a commitment to our customers by providing some of the highest quality products available in the market today.

Our product lines include products for oilfield, industrial, water well, automotive, marine, fishing, petrochemical, and agricultural markets. At present, Oil Center Research International, L.L.C.

can offer a complete line of environmentally safe products for all industries and applications.

Over the last 50 years, Oil Center Research International, L.L.C.'s success is attributable to the strong relationships we have built with our customers as well as the commitment to respond to our customers' needs with the highest quality products and service. Over the years, the industry has presented many challenges, but with wonderful customer support and the dedication of the Oil Center Research family, the Company has continued its success.

Oil Center Research International, L.L.C.
800.549.2407 | 337.993.3559
info@oilcenter.com
www.oilcenter.com/international



Oil Center Research International, L.L.C.
is a team committed to quality service
and products in an ecologically balanced
global marketplace.

LUBRICANTS FOR STUDS & BOLTS

101EU Film Forming Lubricant is a premium quality highly concentrated lubricant that resists the corrosive effects of downhole chemicals. 101EU is made with LIQUILON®, which enhances the lubricity and extreme pressure properties.

101LT is a premium quality lubricant that resists the corrosive effects of downhole chemicals in low temperature applications. *Liquid-O-Ring*® 101LT is thermally stable and inert.

101SYN Synthetic Lubricant Concentrate is a premium quality lubricant made with LIQUILON®, which exhibits excellent low temperature properties, chemical inertness, and film forming capabilities. 101SYN provides instant lubrication in the critical moments of start and stop service.

115 Pure Graphite is a thread compound that protects threads on oil, gas, and steam lines while providing a permanent, non-hardening lubricating seal.

PM1400 MILITARY GREASE meets the most demanding industrial and commercial needs. PM1400 MILITARY GREASE is water-resistant and reduces washout. It also resists pounding out under high shock load, and reduces wear on equipment.

PM2400 High Shock Load Lubricant is a synthetic, water-resistant, all-season lubricant that will reduce washouts. It resists pounding out under high shock load and reduces wear on equipment.

LUBRICATING SEALANTS

404EU is an all-purpose lubricant and sealant for applications that require the best lubrication available. Lubon 404EU's processing and formulation enable it to provide a versatility not found in conventional lubricants.

404LT Low Temperature Lubricant and Sealant is an arctic grade premium lubricant and sealant for pipe threads 2" or smaller. It is used as a dressing for gaskets, O-rings, and packings. Lubon 404LT resists the corrosive effects of downhole conditions and has excellent thermal stability.

404SYN is the only premium, synthetic lubricant and sealant made with LIQUILON® that services temperatures to 400°F (204°C) and pressures to 10,000 psi.

404SYN/ES is an environmentally safe, synthetic lubricant and sealant. This lubricant and sealant is manufactured without any zinc oxide. Made with LIQUILON®, 404SYN/ES services temperatures to 400°F (204°C) and pressures to 10,000 psi.

167ML50 is a premium, anti-seize, anti-gall thread lubricant for use on stainless steel and high corrosion resistant metal/alloy pipe, including chromium, nickel, and Monel.

ANTI-SEIZE COMPOUNDS

HT-1800 Pure Copper Compound is a high temperature, anti-seize compound, that is manufactured with the highest quality copper dust for applications at temperatures up to 1800°F (982°C). HT-1800 contains no lead or graphite.

HT-2001 is a high temperature, anti-seize thread compound, solid film lubricant for applications as high as 2000°F (1093°C). It has superior lubricating abilities.

TC30 is a premium grade non-conductive, anti-galling thread compound. This non-metallic compound contains fibers and extreme pressure and anti-wear additives in a complex base grease for increased performance capabilities. TC30 provides superior adhesion to wet joints and is resistant to water and most drilling muds.

WLR111 is a product specifically designed to replace white lead. It contains no metallic lead or lead oxide and is made with LIQUILON®.

**Over 1,000 products
serving industries
worldwide**

**Visit our website for our
complete product line
and more information**

