



130

WATER DISPLACER AND CORROSION INHIBITOR

- GEAR OILS
- MOTOR OILS
- HYDRAULIC OILS
- PIPE COATINGS
- THREAD SEALANTS
- BEARING GREASES
- SPECIALTY GREASES
- THREAD COMPOUNDS
- SUCKER ROD COATINGS
- OUTSIDE PRESERVATIVES
- WIRELINE GREASE SEALS
- CLEANERS & DEGREASERS
- PIPE STORAGE COMPOUNDS
- RUST & CORROSION INHIBITORS
- THREAD LOCKING COMPOUNDS
- VALVE LUBRICANTS & SEALANTS
- TOOL JOINT & DRILL COLLAR COMPOUNDS

PRODUCT DESCRIPTION

Liquid-O-Ring 130 is formulated as a dual purpose water displacer and corrosion inhibitor. *Liquid-O-Ring* 130 has an affinity for water by seeking out its particles of moisture from the surface and removing it through evaporation. This product has unique creeping and penetrating properties which not only seek out and remove moisture, but leaves a corrosion preventive film on the surface. This anti-corrosion film is transparent and non-staining. *Liquid-O-Ring* 130 is recommended as a surface conditioner prior to applying thread compounds to threads.

BENEFITS

- Protects newly machined parts from corrosive effects of moisture
- Removes moisture from porous metal surfaces
- Leaves surfaces with a corrosion preventive film
- Penetrates rusted surfaces
- Leaves a residual film
- Non-staining

APPLICATION

Liquid-O-Ring 130 is used on threads, newly machined parts, tools, and sliding metal surfaces.

130 may be applied by hand spraying or using a paint brush. Threads should be clean or newly machined. Apply storage compound to 130 treated threads and install standard thread protectors for best results.

TYPICAL OBSERVATIONS

Color	Light Amber
Odor	Solvent
Density, lb/gal @ 77°F (25°C)	6.50
Specific Gravity, @ 77°F (25°C)	0.78
Flash Point, ASTM D-92	105°F (40°C)
Viscosity, ASTM D-1200	
#4 Ford cup @ 77°F (25°F)	9 sec
Recommended Film Thickness	0.10 mil
Approximate Coverage, ft ² /gal	400
Shelf Life (unopened container)	One year

RELATED PRODUCTS

- MD-50 Moisture Displacer
- 1030 Water Soluble Corrosion Inhibitor Concentrate for Cables
- 1031 Water Soluble Corrosion Inhibitor Concentrate for Cables
- 797 Wireline Spray Corrosion Inhibitor
- 797B Blue Line Spray Corrosion Inhibitor

COVERAGE	
PIPE SIZE	JOINTS
1"	2400
2 ⁷ / ₈ "	1200
4 ¹ / ₂ "	750
7 ⁵ / ₈ "	400
9 ⁵ / ₈ "	300
13 ³ / ₈ "	250
20"	150

