



Liquid-O-Ring®*

YOUR SUPER CENTER FOR OVER 1,000 TOP PERFORMANCE PRODUCTS SERVING INDUSTRIES WORLDWIDE

WWW.OILCENTER.COM

502

STEP II

Biodegradable Car And Truck Wash



- GEAR OILS
- MOTOR OILS
- HYDRAULIC OILS
- PIPE COATINGS
- THREAD SEALANTS
- BEARING GREASES
- SPECIALTY GREASES
- THREAD COMPOUNDS
- SUCKER ROD COATINGS
- OUTSIDE PRESERVATIVES
- WIRELINE GREASE SEALS
- CLEANERS & DEGREASERS
- PIPE STORAGE COMPOUNDS
- RUST & CORROSION INHIBITORS
- THREAD LOCKING COMPOUNDS
- VALVE LUBRICANTS & SEALANTS
- TOOL JOINT & DRILL COLLAR COMPOUNDS

PRODUCT DESCRIPTION

502 Step II is a highly concentrated, biodegradable, green liquid detergent specially formulated for the removal of grease, grime, oil, and other soils from trucks, tractors, farm equipment, and other industrial vehicles. This non-abrasive, water-based detergent is safe on most washable surfaces including painted surfaces, laminates, and many plastics.

502 Step II I is an excellent follow-up product to 9641 Wash I. 9641 Wash I is used to remove oxidation and stains encountered when cleaning tractor trailer trucks. 502 Step II penetrates soils and provides a bright finish. The two-step wash system is used primarily on road equipment cleaning.

502 Step II is very effective in the removal of love bugs from vehicles.

BENEFITS

- Biodegradable
- Highly concentrated
- Penetrates soils
- Mixes instantly with water
- Non-abrasive
- Apply by spray or soaking
- Provides a bright finish
- Economical

APPLICATION

Using the appropriate dilution 502 Step II may be applied using pressure washing equipment. It may also be used in manual washing operations for hard to remove soils. 502 Step II provides a very economical solution.

When used in pressure washer, concentration will vary from 2 to 8 oz of 502 Step II per gallon of water. Hot water will aid in cleaning. In an automatic car wash operation, concentration may be 1:50 to 1:75. When used with 501 Step I concentration of 502 Step II may be 1:50 to 1:10.

TYPICAL OBSERVATIONS

Appearance	Liquid
Color	Green
Odor	Mild
pH	12-13
Density, lb/gal @ 77°F (25°C)	8.9
Specific Gravity	1.09
Viscosity, ASTM D-1200	
#4 Ford cup @ 77°F (25°F)	9-11 sec
Solubility in Water	Complete
Shelf Life (unopened container)	One year

RELATED PRODUCTS

9651 Wash II



© 2012, BALMAR LLC Made in U.S.A.

WARRANTY Because the conditions of use and the supervision of application are beyond our control, we assume no liability for any product failure or other damage beyond the purchase price of the material furnished by us. No agent, representative, or employee of this Company is authorized to change this provision, which relates to all goods delivered, whether sold, delivered as samples, or otherwise. Each user should independently determine the suitability of this product based on their specific application.

Manufactured by

BALMAR LLC

616 WEST PONT DES MOUTON ROAD | LAFAYETTE, LA 70507

Sales Locations:

LAFAYETTE, LA | HOUSTON, TX | LONGVIEW, TX | MIDLAND, TX | OKLAHOMA CITY, OK

*Registered trade name of Oil Center Research, Inc. 05/21/19

The product information and specifications listed in this publication are constantly being updated to keep up with government regulations and technology changes. Please visit our web site, www.oilcenter.com, or contact your Account Representative for the most current information relating to this product.