



573

RIG WASHING COMPOUND

- GEAR OILS
- MOTOR OILS
- HYDRAULIC OILS
- PIPE COATINGS
- THREAD SEALANTS
- BEARING GREASES
- SPECIALTY GREASES
- THREAD COMPOUNDS
- SUCKER ROD COATINGS
- OUTSIDE PRESERVATIVES
- WIRELINE GREASE SEALS
- CLEANERS & DEGREASERS
- PIPE STORAGE COMPOUNDS
- RUST & CORROSION INHIBITORS
- THREAD LOCKING COMPOUNDS
- VALVE LUBRICANTS & SEALANTS
- TOOL JOINT & DRILL COLLAR COMPOUNDS

PRODUCT DESCRIPTION

573 Rig Washing Compound is an excellent, heavy-duty, white cleaning compound. It removes dirt, grease, and oil from rig equipment and fixtures, helping to reduce the risk of serious accidents associated with an unclean work environment. 573 Rig Washing Compound is also an excellent laundry detergent for hand washing heavily soiled clothes. 573 Rig Washing Compound works effectively in hot or cold, hard or soft, fresh or salt water. It may be applied by hand or used in washing machines. 573 Rig Washing Compound contains no caustics or harsh chemicals. In its diluted form 573 Rig Washing Compound is biodegradable.

BENEFITS

- Biodegradable in diluted form
- Fast acting
- Concentrated
- Versatile
- Contains no caustics or harsh chemicals

APPLICATION

573 Rig Washing Compound may be used with pressure spray and mechanical scrubbing equipment, in concentrated injection systems, or by hand. For sensitive skin, gloves are advisable.

Add 4 oz (118 ml) to 8 oz (237 ml) of 573 RIG WASHING COMPOUND to each gallon of water. Apply to surface and rinse with water.

For laundry detergent, add ½ cup to 1 cup of 573 Rig Washing Compound per wash load, depending on size of load and amount of soil.

TYPICAL OBSERVATIONS

pH (1% solution)	11.4
Color	White
Appearance	Powder
Odor	Citrus
Specific Gravity	1.71
Density, lb/gal	14.30
Solubility in Water	Complete
Shelf Life (unopened container)	Six Months

RELATED PRODUCTS

- 583 Rig Wash Compound
- 950 Rig Clean Rig Washing Compound
- 9561 Rig Washing Compound
- 9562 Rig Wash

