

# 600/3 VALVE LAST

## Extreme Temperature Valve Lubricant and Sealant

### PRODUCT DESCRIPTION

600/3 Valve Last is a synthetic valve lubricant and sealant with graphite for extreme temperature application. 600/3 Valve Last exhibits excellent resistance to washout from hot oils, hydrocarbons, asphalts, and solvents. Corrosion inhibitors and extreme pressure additives in 600/3 Valve Last provide extended life and compatibility under harsh conditions.

600/3 Valve Last prevents galling and seizing and provides a tighter seal. It will not melt, drip, or separate.

### APPLICATION

600/3 Valve Last is recommended for plug, gate, ball, and high pressure valves, valves in extreme temperature service, and valves servicing hot oils or asphalts, solvents, and hydrocarbons.

600/3 Valve Last is used in the following industries: hot oil companies, solvent manufacturers/processors, gathering systems, utilities, cracking and reforming plants, chemical processors, refineries, valve manufacturers, and valve rebuilders.

### TYPICAL OBSERVATIONS

Color	Black
Texture	
Bulk	Smooth
Stick	Stick
Density, lb/gal @ 77°F (25°C)	
Bulk	8.25
Stick	8.25
Specific Gravity, @ 77°F (25°C)	
Bulk	0.989
Stick	0.989
Dropping Point, ASTM, D-2265	>500°F (>260°C)
Flash Point, ASTM D-92	445°F (229°C)
Penetration, ASTM D-217 worked @ 77°F (25°C)	
Bulk	265
Stick	85
Base Oil Viscosity, @ 40°C cSt	586
Oil Separation, ASTM D-1742 % wt. loss	<2.0
Corrosion Preventive Properties, ASTM D-1742 @ 125°F (51°C)	Pass
Water Washout Characteristics, ASTM D-1264 @ 100°F (37°C)	Nil
Oxidation Stability, ASTM D-942 @ 210°F (98°C), 72 hrs. PSI Loss	10
Temperature Range	-40°F to >400°F (-40°C to >204°C)
Shelf Life (unopened container)	Two years

### BENEFITS

- Prevents seizing
- Provides a tighter seal
- Resistant to H<sub>2</sub>S and CO<sub>2</sub>
- Non-melting
- Corrosion inhibited
- High temperature application
- Will not separate
- Insoluble in water

### SERVICE RECOMMENDATIONS

- Acid solutions
- Diesel or kerosene
- Sour oil or gas
- Sulphanated oils

FRAC

FLUSH

ARCTIC

STORAGE

SEALANTS

CLEANERS

ASSEMBLY

BALL VALVE  
LUBRICANTS

GATE VALVE  
LUBRICANTS

PLUG VALVE  
LUBRICANTS

STICK PACKING



*Liquid-O-Ring*®\*

© 2021, BALMAR LLC  
WARRANTY Because the conditions of use and the supervision of application are beyond our control, we assume no liability for any product failure or other damage beyond the purchase price of the material furnished by us. No agent, representative, or employee of this Company is authorized to change this provision, which relates to all goods delivered, whether sold, delivered as samples, or otherwise. Each user should independently determine the suitability of this product based on their specific application.

\*Registered Tradename of Oil Center Research, Inc.



WWW.OILCENTER.COM

Manufactured by  
**BALMAR LLC**

616 WEST PONT DES MOUTON ROAD | LAFAYETTE, LA 70507

Sales Locations:  
LAFAYETTE, LA | HOUSTON, TX | LONGVIEW, TX | MIDLAND, TX | OKLAHOMA CITY, OK

Made in U.S.A.

The product information and specifications listed in this publication are constantly being updated to keep up with government regulations and technology changes. Please visit our website, [www.oilcenter.com](http://www.oilcenter.com), or contact your Account Representative for the most current information relating to this product.