



# 765

## “GREASE SEAL”

### Specialized Wireline Lubricant and Sealant for Specific Temperatures

#### PRODUCT DESCRIPTION

765 “Grease Seal” is a series of specialized wireline lubricants and sealants. These products are manufactured polymer sealants that maintains a 16-20 viscosity at the recommended temperature range. 765 “Grease Seal” provides the necessary corrosion inhibitors to effect long range protection to the wireline. 765 “Grease Seal” is inhibited against the corrosive effects of acids, caustics, salt water, and H<sub>2</sub>S.

If the operator knows the approximate temperatures in which his unit will be operating, a specific 765 “Grease Seal” may be ordered which will sustain its viscosity at the operational temperatures. The 765 “Grease Seal” series of products allow the operator to be more selective in choosing a product to meet his operating conditions.

#### APPLICATION

765 “Grease Seal” is applied to grease injection control heads and cable lubricators. 765 “Grease Seal” is manufactured for use in arctic conditions. Inhibitors and additives used are designed to be compatible with products used under arctic conditions.

#### RELATED PRODUCTS

- 766 CO<sub>2</sub>-Resistant Wireline Grease Seal
- 770 Grease Seal 16 viscosity
- 774 Grease Seal 20 viscosity
- 774/41® Grease Seal with extra corrosion inhibitors 20 viscosity
- 778 Super Grease Seal 28 viscosity
- 779 Extreme Temperature Supreme Grease Seal 30 viscosity
- 780 Biodegradable Grease Seal 12, 16, 20, and 30 viscosities
- 784 Concentrated, Biodegradable Grease Seal 24 viscosity
- 800 Biodegradable, Synthetic Grease 10, 12, 16, 20, 24, and 28 viscosities

#### BENEFITS

- Maintains viscosity at temperature range
- Corrosion inhibitors for long range protection
- Protects corrosive effects of acids, caustics, salt water, and H<sub>2</sub>S

#### TYPICAL OBSERVATIONS

	765A	765D	765F	765G
Viscosity, Kinematic @ 40°C, cSt	45–55	175–185	450–550	1720–2120
Viscosity Index	35	115	150	254
Color	Yellow	Yellow	Yellow	Yellow
Texture	Tacky Liquid	Tacky Liquid	Tacky Liquid	Tacky Liquid
Odor	Mild	Mild	Mild	Mild
API Gravity, @ 60°F (15°C)	32	32	32	32
Density Range, lb/gal @ 77°F (25°C)	7.00–7.50	7.00–7.50	7.00–7.50	7.00–7.50
Specific Gravity Range, @ 77°F (25°C)	0.839–0.899	0.839–0.899	0.839–0.899	0.839–0.899
Flash Point, ASTM D-92	390°F (198°C)	390°F (198°C)	390°F (198°C)	390°F (198°C)
Pour Point, ASTM D-97	-65°F (-54°C)	-15°F (-26°C)	-5°F (-21°C)	5°F (-15°C)
Rust Preventive Test, ASTM D-3603 @ 140°F (60°C)	Pass	Pass	Pass	Pass
Temperature Range	-35°F to -10°F (-37°C to -23°C)	-20°F to 0°F (-29°C to -18°C)	5°F to 25°F (-15°C to -4°C)	45°F to 80°F (7°C to 27°C)
Shelf Life (unopened container)	Four years	Four years	Four years	Four years

- GEAR OILS
- MOTOR OILS
- HYDRAULIC OILS
- PIPE COATINGS
- THREAD SEALANTS
- BEARING GREASES
- SPECIALTY GREASES
- THREAD COMPOUNDS
- SUCKER ROD COATINGS
- OUTSIDE PRESERVATIVES
- WIRELINE GREASE SEALS
- CLEANERS & DEGREASERS
- PIPE STORAGE COMPOUNDS
- RUST & CORROSION INHIBITORS
- THREAD LOCKING COMPOUNDS
- VALVE LUBRICANTS & SEALANTS
- TOOL JOINT & DRILL COLLAR COMPOUNDS



© 2021, BALMAR LLC Made in U.S.A.  
**WARRANTY** Because the conditions of use and the supervision of application are beyond our control, we assume no liability for any product failure or other damage beyond the purchase price of the material furnished by us. No agent, representative, or employee of this Company is authorized to change this provision, which relates to all goods delivered, whether sold, delivered as samples, or otherwise. Each user should independently determine the suitability of this product based on their specific application.

Manufactured by  
**BALMAR LLC**

616 WEST PONT DES MOUTON ROAD | LAFAYETTE, LA 70507

Sales Locations:  
 LAFAYETTE, LA | HOUSTON, TX | LONGVIEW, TX | MIDLAND, TX | OKLAHOMA CITY, OK

\*Registered trade name of Oil Center Research, Inc.  
 The product information and specifications listed in this publication are constantly being updated to keep up with government regulations and technology changes. Please visit our web site, [www.oilcenter.com](http://www.oilcenter.com), or contact your Account Representative for the most current information relating to this product.