



777

PREMIUM LIFT BOAT GEAR GREASE

- GEAR OILS
- MOTOR OILS
- HYDRAULIC OILS
- PIPE COATINGS
- THREAD SEALANTS
- BEARING GREASES
- SPECIALTY GREASES
- THREAD COMPOUNDS
- SUCKER ROD COATINGS
- OUTSIDE PRESERVATIVES
- WIRELINE GREASE SEALS
- CLEANERS & DEGREASERS
- PIPE STORAGE COMPOUNDS
- RUST & CORROSION INHIBITORS
- THREAD LOCKING COMPOUNDS
- VALVE LUBRICANTS & SEALANTS
- TOOL JOINT & DRILL COLLAR COMPOUNDS

PRODUCT DESCRIPTION

777 Premium Lift Boat Gear Grease is an NLGI Grade 3 grease manufactured especially for extra heavy duty applications. This black, extreme-pressure grease offers excellent water-resistant properties as well as excellent adhesive and cohesive properties. Although it has a very tacky texture 777 Premium Lift Boat Gear Grease remains very smooth and buttery. The presence of graphite and molybdenum disulfide (moly) allows 777 Premium Lift Boat Gear Grease to form a protective lubricant coating under heavy loads to prevent metal-to-metal contact. This lubricant has excellent load carrying capability, is very resistant to water washout, and is non-corrosive to copper and steel. 777 Premium Lift Boat Gear Grease services temperatures from -8°F (-22°C) up to 275°F (135°C).

BENEFITS

- Especially for extra heavy duty applications
- Excellent in extreme-pressure conditions
- Excellent water resistance
- Non-corrosive to copper and steel
- Services temperatures from -8°F (-22°C) up to 275°F (135°C)
- Versatile
- Excellent adhesive and cohesive properties
- Very tacky texture yet remains smooth and buttery
- Forms a protective lubricant coating
- Excellent load carrying capability
- Contains graphite and molybdenum disulfide (moly)

APPLICATION

777 Premium Lift Boat Gear Grease is manufactured especially for extra heavy duty applications. The excellent adhesive and cohesive properties of 777 Premium Lift Boat Gear Grease make it an ideal lubricant/dressing for open gears, rock-drill stems, marine ways, underwater equipment, and industrial applications where extreme resistance to water washout is desirable.

TYPICAL OBSERVATIONS

Color	Black
Texture	Smooth Paste
Dropping Point, ASTM 2265	209°F (98°C)
Density, lb/gal @ 77°F (25°C)	7.72
Specific Gravity, @ 77°F (25°C)	0.925
Flash Point, ASTM D-92	>375°F (>190°C)
Penetration, ASTM D-217	
worked @ 77°F (25°C)	220
Water Washout Resistance, ASTM D-1264 @ 100°F (37°C)	Nil
Evaporation Loss, ASTM D-972 @ 210°F (98°C)	Nil
Oil Separation, ASTM D-1742 @ 77°F (25°C)	Nil
4-Ball, EP Weld Load, Kgf, ASTM D-2596	400 Pass 500 Weld
Temperature Range	-8°F up to 275°F (-22°C up to 135°C)
Shelf Life (unopened container)	Two years

RELATED PRODUCTS

- 737 Leg Grease
- 757 Lift Boat Gear Lube



© 2012, BALMAR LLC Made in U.S.A.
WARRANTY Because the conditions of use and the supervision of application are beyond our control, we assume no liability for any product failure or other damage beyond the purchase price of the material furnished by us. No agent, representative, or employee of this Company is authorized to change this provision, which relates to all goods delivered, whether sold, delivered as samples, or otherwise. Each user should independently determine the suitability of this product based on their specific application.

Manufactured by
BALMAR LLC

616 WEST PONT DES MOUTON ROAD | LAFAYETTE, LA 70507

Sales Locations:
 LAFAYETTE, LA | HOUSTON, TX | LONGVIEW, TX | MIDLAND, TX | OKLAHOMA CITY, OK

*Registered trade name of Oil Center Research, Inc. 11/19/13
 The product information and specifications listed in this publication are constantly being updated to keep up with government regulations and technology changes. Please visit our web site, www.oilcenter.com, or contact your Account Representative for the most current information relating to this product.