



Liquid-O-Ring®*

YOUR SUPER CENTER FOR OVER 1,000 TOP PERFORMANCE PRODUCTS SERVING INDUSTRIES WORLDWIDE

WWW.OILCENTER.COM

PROTEKTO-COAT®

799



ENVIRONMENTALLY ACCEPTABLE INTERNAL & EXTERNAL COATING

- GEAR OILS
- MOTOR OILS
- HYDRAULIC OILS
- PIPE COATINGS
- THREAD SEALANTS
- BEARING GREASES
- SPECIALTY GREASES
- THREAD COMPOUNDS
- SUCKER ROD COATINGS
- OUTSIDE PRESERVATIVES
- WIRELINE GREASE SEALS
- CLEANERS & DEGREASERS
- PIPE STORAGE COMPOUNDS
- RUST & CORROSION INHIBITORS
- THREAD LOCKING COMPOUNDS
- VALVE LUBRICANTS & SEALANTS
- TOOL JOINT & DRILL COLLAR COMPOUNDS

PRODUCT DESCRIPTION

Protekto-Coat® 799 is a vegetable oil base internal and external pipe coating formulated to protect the ID and OD of tubulars from the harmful affects of corrosion during storage. Protekto-Coat® 799 is recommended as an easy to apply, environmentally friendly ID and OD coating for short term storage by rental tool companies and used pipe dealers. It will not flow and build up on the lower or bottom portion of the pipe if properly applied following application instructions. Protekto-Coat® 799 also provides high resistance to corrosion. Protekto-Coat® 799 is easy and economical to use. Protekto-Coat® 799 contains biodegradable oil, inhibitors, and a petroleum solvent. After application, the solvent evaporates, leaving an environmentally friendly protective coating to the metal surface.

BENEFITS

- Provides excellent rust protection
- Economical
- Excellent dip tank coating
- Environmentally friendly

APPLICATION

Protekto-Coat® 799 is easy and economical to use in most dip tank applications. It may also be applied with air or airless spray methods. After applying Protekto-Coat® 799, remove excess coating by blowing out the pipe with air and placing the pipe at an angle to allow coating to run out the end before installation of thread protectors. If coating is not completely drained, gumming will occur on the lower side of the pipe.

Use Protekto-Coat® 799 on macaroni tubing, casing, line pipe, drill pipe, drill collars, small tools, or equipment.

TYPICAL OBSERVATIONS

Color	Golden Yellow
Texture	Liquid
Density, lb/gal @ 77°F (25°C)	7.26
Specific Gravity, @ 77°F (25°C)	0.87
Viscosity, ASTM D-1200	
#4 Ford cup @ 77°F (25°F)	13 sec
Flash Point, ASTM D-93	105°F (40°C)
VOC, lb/gal	2.27
Shelf Life (unopened container)	One year

RELATED PRODUCTS

- 710N Biodegradable Internal Drill Pipe Coating
- 725 Internal Coating
- 789 Internal Coating
- 908 Thick Internal Coating
- 910 Internal Pipe Coating
- 938 Flexible Internal/External Coating
- 690 Aqua Cure Corrosion Inhibitor for Brine Solutions
- 935 Concentrated Rust Inhibitor for Hydrostatic Testing



© 2012, BALMAR LLC Made in U.S.A.

WARRANTY Because the conditions of use and the supervision of application are beyond our control, we assume no liability for any product failure or other damage beyond the purchase price of the material furnished by us. No agent, representative, or employee of this Company is authorized to change this provision, which relates to all goods delivered, whether sold, delivered as samples, or otherwise. Each user should independently determine the suitability of this product based on their specific application.

Manufactured by

BALMAR LLC

616 WEST PONT DES MOUTON ROAD | LAFAYETTE, LA 70507

Sales Locations:

LAFAYETTE, LA | HOUSTON, TX | LONGVIEW, TX | MIDLAND, TX | OKLAHOMA CITY, OK

*Registered trade name of Oil Center Research, Inc. 10/25/16

The product information and specifications listed in this publication are constantly being updated to keep up with government regulations and technology changes. Please visit our web site, www.oilcenter.com, or contact your Account Representative for the most current information relating to this product.