



855

BAR & CHAIN LUBRICANT

- GEAR OILS
- MOTOR OILS
- HYDRAULIC OILS
- PIPE COATINGS
- THREAD SEALANTS
- BEARING GREASES
- SPECIALTY GREASES
- THREAD COMPOUNDS
- SUCKER ROD COATINGS
- OUTSIDE PRESERVATIVES
- WIRELINE GREASE SEALS
- CLEANERS & DEGREASERS
- PIPE STORAGE COMPOUNDS
- RUST & CORROSION INHIBITORS
- THREAD LOCKING COMPOUNDS
- VALVE LUBRICANTS & SEALANTS
- TOOL JOINT & DRILL COLLAR COMPOUNDS

PRODUCT DESCRIPTION

855 Bar and Chain Lubricant provides protection under all operating conditions. 855 Bar and Chain Lubricant stays on the bar and chain longer by forming a tough, continuous lubricating film that protects against wear, reduces consumption, and increases the life of the bar and chain. Formulated to resist dripping, wash-off, and shear-off, 855 Bar and Chain Lubricant prevents rust and corrosion as well as reduce friction and heat build-up on the bar and chain. The presence of EP additives allow 855 Bar and Chain Lubricant to withstand pressure and minimize metal-to-metal contact thereby reducing noise.

TYPICAL OBSERVATIONS

Color	Green
Appearance	Liquid
Odor	Mild Petroleum
Density, @ 77°F (25°C)	7.48
Specific Gravity	0.896
Flash Point, ASTM D-92	>400°F (>204°C)
Viscosity,	
@ 40°C cSt	370
@ 100°C cSt	30
Viscosity Index	113
Solubility in Water	<1
Shelf Life (unopened container)	Two Years

BENEFITS

- EP additives
- Prevents rust and corrosion
- Reduces consumption
- Stays on chain longer
- Reduces friction and wear
- Increases chain, bar, and sprocket life
- Resists dripping, wash-off, and shear-off

APPLICATION

855 Bar and Chain Lubricant may be used on open gears, chains, cables, wire ropes, and other areas where the lubricant is exposed to atmospheric conditions.

