



Liquid-O-Ring®*

YOUR SUPER CENTER FOR OVER 1,000 TOP PERFORMANCE PRODUCTS SERVING INDUSTRIES WORLDWIDE

WWW.OILCENTER.COM

PROTEKTO-COAT®

912

CLEAR EXTERNAL PIPE COATING

- GEAR OILS
- MOTOR OILS
- HYDRAULIC OILS
- PIPE COATINGS
- THREAD SEALANTS
- BEARING GREASES
- SPECIALTY GREASES
- THREAD COMPOUNDS
- SUCKER ROD COATINGS
- OUTSIDE PRESERVATIVES
- WIRELINE GREASE SEALS
- CLEANERS & DEGREASERS
- PIPE STORAGE COMPOUNDS
- RUST & CORROSION INHIBITORS
- THREAD LOCKING COMPOUNDS
- VALVE LUBRICANTS & SEALANTS
- TOOL JOINT & DRILL COLLAR COMPOUNDS

PRODUCT DESCRIPTION

Protekto-Coat® 912 is an economical, solvent base external coating formulated to provide long-term protective coating to external tubular surfaces while the pipe is in storage. Protekto-Coat® 912 dries to a clear, glossy finish and has excellent humidity and salt spray resistance.

Protekto-Coat® 912 is for use on external tubular surfaces while pipe is in storage.

BENEFITS

- Gives high gloss for excellent appearance
- Dries fast to a clear film
- Contains a bonding agent
- Ready to spray
- Allows visual inspection of pipe markings
- Excellent humidity and salt spray resistance

TYPICAL OBSERVATIONS

Type	Alkyd Resin
Appearance	Liquid
Color	Amber
Gloss	High
Odor	Mild Hydrocarbon
Viscosity, #4 cup @ 77°F (25°C)	16–18 sec
Density, lb/gal @ 77°F (25°C)	7.21
Specific Gravity, @ 77°F (25°C)	0.864
Drying Time, ASTM D-5895	15 min
Flash Point, ASTM D-93	105°F (40.5°C)
VOC lb/gal	4.75
Salt Spray Test, ASTM B-117 (200 hrs)	Pass
Shelf Life (unopened container)	One year

RELATED PRODUCTS

- 922 External Pipe Coating, (Black, Asphalt-based)
- 923 External Pipe Coating (Amber, Glossy)



© 2012, BALMAR LLC Made in U.S.A.

WARRANTY Because the conditions of use and the supervision of application are beyond our control, we assume no liability for any product failure or other damage beyond the purchase price of the material furnished by us. No agent, representative, or employee of this Company is authorized to change this provision, which relates to all goods delivered, whether sold, delivered as samples, or otherwise. Each user should independently determine the suitability of this product based on their specific application.

Manufactured by

BALMAR LLC

616 WEST PONT DES MOUTON ROAD | LAFAYETTE, LA 70507

Sales Locations:

LAFAYETTE, LA | HOUSTON, TX | LONGVIEW, TX | MIDLAND, TX | OKLAHOMA CITY, OK

*Registered trade name of Oil Center Research, Inc. 09/25/17

The product information and specifications listed in this publication are constantly being updated to keep up with government regulations and technology changes. Please visit our web site, www.oilcenter.com, or contact your Account Representative for the most current information relating to this product.