PROTEKTO-COAT® 922

BLACK EXTERNAL PIPE COATING

GEAR OILS
MOTOR OILS
HYDRAULIC OILS
PIPE COATINGS
THREAD SEALANTS
BEARING GREASES
SPECIALTY GREASES
THREAD COMPOUNDS
SUCKER ROD COATINGS
OUTSIDE PRESERVATIVES
WIRELINE GREASE SEALS
CLEANERS & DEGREASERS
PIPE STORAGE COMPOUNDS
RUST & CORROSION INHIBITORS
THREAD LOCKING COMPOUNDS
VALVE LUBRICANTS & SEALANTS
TOOL JOINT & DRILL COLLAR COMPOUNDS

PRODUCT DESCRIPTION

Protekto-Coat® 922 is a black, asphalt-based external coating formulated to provide an excellent long-term protective coating to external tubular surfaces while the pipe is in storage. Protekto-Coat® 922 provides economical protection against rust and corrosion. Recommended for tubing, casing, drill collars, and line pipe,Protekto-Coat® 922 dries to a tough, durable film that seals the surface from air, moisture, and the elements.

Protekto-Coat® 922 applications include drill pipe, wash pipe, pump columns, work strings or other applications where medium term protection is required.

BENEFITS

- **Economical**
- **No visible pipe imperfections**
- **Excellent adhesion with only minimal surface preparation**
- **Humidity and salt resistant**
- **Prevents rusting**

TYPICAL OBSERVATIONS

Type	Asphaltic
Color	Black
Odor	Mild Hydrocarbon
Viscosity, #4 cup @ 77°F (25°C)	15–17 sec
Density, lb/gal @ 77°F (25°C)	7.00
Specific Gravity, @ 77°F (25°C)	0.839
Drying Time, ASTM D-5895	10–15 min
Flash Point, ASTM D-93	105°F (40.5°C)
VOC, lb/gal	3.89
Shelf Life (unopened container)	One year

RELATED PRODUCTS

912 External Pipe Coating (Clear, Glossy)
923 External Pipe Coating (Amber, Glossy)

© 2021, BALMAR LLC Made in U.S.A.

WARRANTY Because the conditions of use and the supervision of application are beyond our control, we assume no liability for any product failure or other damage beyond the purchase price of the material furnished by us. No agent, representative, or employee of this Company is authorized to change this provision, which relates to all goods delivered, whether sold, delivered as samples, or otherwise. Each user should independently determine the suitability of this product based on their specific application.

Manufactured by
BALMAR LLC
616 WEST PONT DES MOUTON ROAD | LAFAYETTE, LA 70507
Sales Locations:
LAFAYETTE, LA | HOUSTON, TX | LONGVIEW, TX | MIDLAND, TX | OKLAHOMA CITY, OK

*Registered trade name of Oil Center Research, Inc.
The product information and specifications listed in this publication are constantly being updated to keep up with government regulations and technology changes. Please visit our web site, www.oilcenter.com, or contact your Account Representative for the most current information relating to this product.