



Liquid-O-Ring®*

YOUR SUPER CENTER FOR OVER 1,000 TOP PERFORMANCE PRODUCTS SERVING INDUSTRIES WORLDWIDE

WWW.OILCENTER.COM

PROTEKTO-COAT® 923

GLOSSY, AMBER EXTERNAL PIPE COATING

PRODUCT DESCRIPTION

Protekto-Coat® 923 is an amber-colored external coating formulated to provide an excellent long-term protective coating to external tubular surfaces while the pipe is in storage. Protekto-Coat® 923 provides a semi-clear finish which allows markings on the pipe to be easily readable. The durable film of Protekto-Coat® 923 has excellent humidity and salt spray resistance.

Protekto-Coat® 923 application includes external tubular surfaces while pipe is in storage.

TYPICAL OBSERVATIONS

Type	Alkyd Resin
Color	Dark Amber
Odor	Mild Hydrocarbon
Viscosity, #4 cup @ 77°F (25°C)	16–18 sec
Density, lb/gal @ 77°F (25°C)	7.21
Specific Gravity, @ 77°F (25°C)	0.864
Drying Time STT (room Temp)	10–15 min
Flash Point, ASTM D-93	105°F (41°C)
Salt Spray Test, ASTM B-117 (200 hrs)	Pass
VOC, lb/gal	4.49
Shelf Life (unopened container)	One year

BENEFITS

- Amber tint gives excellent cosmetic appearance
- Good adhesion
- Humidity and salt spray resistant
- Prevents rusting

RELATED PRODUCTS

- 912 External Pipe Coating (Clear, Glossy)
- 922 External Pipe Coating (Black, Asphalt-based)

- GEAR OILS
- MOTOR OILS
- HYDRAULIC OILS
- PIPE COATINGS
- THREAD SEALANTS
- BEARING GREASES
- SPECIALTY GREASES
- THREAD COMPOUNDS
- SUCKER ROD COATINGS
- OUTSIDE PRESERVATIVES
- WIRELINE GREASE SEALS
- CLEANERS & DEGREASERS
- PIPE STORAGE COMPOUNDS
- RUST & CORROSION INHIBITORS
- THREAD LOCKING COMPOUNDS
- VALVE LUBRICANTS & SEALANTS
- TOOL JOINT & DRILL COLLAR COMPOUNDS



© 2012, BALMAR LLC Made in U.S.A.

WARRANTY Because the conditions of use and the supervision of application are beyond our control, we assume no liability for any product failure or other damage beyond the purchase price of the material furnished by us. No agent, representative, or employee of this Company is authorized to change this provision, which relates to all goods delivered, whether sold, delivered as samples, or otherwise. Each user should independently determine the suitability of this product based on their specific application.

Manufactured by

BALMAR LLC

616 WEST PONT DES MOUTON ROAD | LAFAYETTE, LA 70507

Sales Locations:

LAFAYETTE, LA | HOUSTON, TX | LONGVIEW, TX | MIDLAND, TX | OKLAHOMA CITY, OK

*Registered trade name of Oil Center Research, Inc. 10/17/16

The product information and specifications listed in this publication are constantly being updated to keep up with government regulations and technology changes. Please visit our web site, www.oilcenter.com, or contact your Account Representative for the most current information relating to this product.