9596

CLEAN DIP

Concentrated Vat Compound

GEAR OILS
MOTOR OILS
HYDRAULIC OILS
PIPE COATINGS
THREAD SEALANTS
BEARING GREASES
SPECIALTY GREASES
THREAD COMPOUNDS
SUCKER ROD COATINGS
OUTSIDE PRESERVATIVES
WIRELINE GREASE SEALS
CLEANERS & DEGREASERS
PIPE STORAGE COMPOUNDS
RUST & CORROSION INHIBITORS
THREAD LOCKING COMPOUNDS
VALVE LUBRICANTS & SEALANTS
TOOL JOINT & DRILL COLLAR COMPOUNDS

PRODUCT DESCRIPTION

9596 Clean Dip is a heavy-duty concentrated vat compound for use in hot or cold temperature dip/soak operations on cast iron, steel, and other hard metals. 9596 Clean Dip removes soils such as paint, grease, and rust from cast iron and steel.

9596 Clean Dip rinses quickly and easily with clean water and can be followed by a corrosion inhibitor, such as Rustless 740, to retard flash rusting.

BENEFITS

- **Concentrated**
- **Heavy-duty**
- **For use in hot or cold temperature operations**
- **Removes paints, grease, and rust (in normal or heated vats)**
- **Rinses quickly and easily with water**
- **Easy to mix**

APPLICATION

9596 Clean Dip may be used in hot or cold temperature dip/soak operations for the removal of paint, grease, and rust from cast iron, steel, and other hard metals.

Use 6 to 10 oz of 9596 Clean Dip per gal of water. Allow to stand at operating temperature for 5 minutes. Remove and rinse prior to handling or black plating. Additional 9596 Clean Dip may be used to increase or renew cleaning strength when necessary. Never add 9596 Clean Dip to solution over 115°F (46°C). If solution is above this temperature, allow to cool. Add 9596 Clean Dip very slowly over entire surface of solution, while stirring gently to avoid splattering.

To determine size of dip tank and volume of water, measure length-width-depth, then multiply by 7.5. Normally 1 pound of 9596 Clean Dip is sufficient solution if to be heated and 2 pounds per gallon of water if used cold.

TYPICAL OBSERVATIONS

Appearance	Free-flowing
Color	White
pH, 5%	13.6
Flash Point	None
Density, lb/gal	10.70
Specific Gravity @ 77°F (25°C)	1.28
Solubility in Water	Soluble
Shelf Life (unopened container)	Six months

RELATED PRODUCTS

530 Dip Clean Concentrated Vat Compound

© 2021, BALMAR LLC Made in U.S.A.

WARRANTY Because the conditions of use and the supervision of application are beyond our control, we assume no liability for any product failure or other damage beyond the purchase price of the material furnished by us. No agent, representative, or employee of this Company is authorized to change this provision, which relates to all goods delivered, whether sold, delivered as samples, or otherwise. Each user should independently determine the suitability of this product based on their specific application.

Manufactured by
BALMAR LLC
616 WEST PONT DES MOUTON ROAD | LAFAYETTE, LA 70507
Sales Locations:
LAFAYETTE, LA | HOUSTON, TX | LONGVIEW, TX | MIDLAND, TX | OKLAHOMA CITY, OK

*Registered trade name of Oil Center Research, Inc.
The product information and specifications listed in this publication are constantly being updated to keep up with government regulations and technology changes. Please visit our web site, www.oilcenter.com, or contact your Account Representative for the most current information relating to this product.