



Liquid-O-Ring®\*

YOUR SUPER CENTER FOR OVER 1,000 TOP PERFORMANCE PRODUCTS SERVING INDUSTRIES WORLDWIDE

WWW.OILCENTER.COM

# PM322

## CABLE GUARD

### Chain & Cable Lubricant

- GEAR OILS
- MOTOR OILS
- HYDRAULIC OILS
- PIPE COATINGS
- THREAD SEALANTS
- BEARING GREASES
- SPECIALTY GREASES
- THREAD COMPOUNDS
- SUCKER ROD COATINGS
- OUTSIDE PRESERVATIVES
- WIRELINE GREASE SEALS
- CLEANERS & DEGREASERS
- PIPE STORAGE COMPOUNDS
- RUST & CORROSION INHIBITORS
- THREAD LOCKING COMPOUNDS
- VALVE LUBRICANTS & SEALANTS
- TOOL JOINT & DRILL COLLAR COMPOUNDS

#### PRODUCT DESCRIPTION

PM322 Cable Guard is an excellent chain and cable lubricant that provides superior rust protection and core lubrication. PM322 Cable Guard has excellent penetrating quality. PM322 Cable Guard dries to a flexible coating on the outside of cables, while staying soft on the inside to reduce friction between cables and strands. It adheres to cables and chains, reducing drip and waste in application with minimum downtime and maintenance cost.

#### BENEFITS

- Superior rust protection and core lubrication
- Dries to a protective film
- Corrosion inhibited
- Excellent adhesion
- Longer life of cables and chains

#### APPLICATION

PM322 Cable Guard may be applied by swabbing, dipping, and spraying. It can also be applied with drip oilers or force-fed applicators. Apply PM322 Cable Guard to lubricate and protect hemp cord, jute, sisal cord, wire cable, and chain.

#### TYPICAL OBSERVATIONS

Type	Asphaltic
Color	Black
Odor	Mild Hydrocarbon
Viscosity, ASTM D-1200	
#4 Ford cup @ 77°F (25°F)	15–17 sec
Density, lb/gal @ 77°F (25°C)	7.00
Specific Gravity @ 77°F (25°C)	0.839
Flash Point, ASTM D-93	105°F (40°C)
Dry Time, ASTM 5895	10–15 min
VOC, lb/gal	3.89
Shelf Life (unopened container)	Two years

#### RELATED PRODUCTS

- 1030 Water Soluble Corrosion Inhibitor Concentrate for Cables
- 1031 Water Soluble Corrosion Inhibitor Concentrate for Cables
- 759 Cable Guard Grease
- 773 Cable Coating
- 783 Biodegradable Marine Cable Coating
- PM322M Cable Guard Chain and Cable Lubricant with Liquid Moly



© 2012, BALMAR LLC Made in U.S.A.

**WARRANTY** Because the conditions of use and the supervision of application are beyond our control, we assume no liability for any product failure or other damage beyond the purchase price of the material furnished by us. No agent, representative, or employee of this Company is authorized to change this provision, which relates to all goods delivered, whether sold, delivered as samples, or otherwise. Each user should independently determine the suitability of this product based on their specific application.

Manufactured by

**BALMAR LLC**

616 WEST PONT DES MOUTON ROAD | LAFAYETTE, LA 70507

Sales Locations:

LAFAYETTE, LA | HOUSTON, TX | LONGVIEW, TX | MIDLAND, TX | OKLAHOMA CITY, OK

\*Registered trade name of Oil Center Research, Inc. 10/25/16

The product information and specifications listed in this publication are constantly being updated to keep up with government regulations and technology changes. Please visit our web site, [www.oilcenter.com](http://www.oilcenter.com), or contact your Account Representative for the most current information relating to this product.