# PM322

## CABLE GUARD

### Chain & Cable Lubricant

GEAR OILS
MOTOR OILS
HYDRAULIC OILS
PIPE COATINGS
THREAD SEALANTS
BEARING GREASES
SPECIALTY GREASES
THREAD COMPOUNDS
SUCKER ROD COATINGS
OUTSIDE PRESERVATIVES
WIRELINE GREASE SEALS
CLEANERS & DEGREASERS
PIPE STORAGE COMPOUNDS
RUST & CORROSION INHIBITORS
THREAD LOCKING COMPOUNDS
VALVE LUBRICANTS & SEALANTS
TOOL JOINT & DRILL COLLAR COMPOUNDS

## PRODUCT DESCRIPTION

PM322 Cable Guard is an excellent chain and cable lubricant that provides superior rust protection and core lubrication. PM322 Cable Guard has excellent penetrating quality. PM322 Cable Guard dries to a flexible coating on the outside of cables, while staying soft on the inside to reduce friction between cables and strands. It adheres to cables and chains, reducing drip and waste in application with minimum downtime and maintenance cost.

## BENEFITS

- **Superior rust protection and core lubrication**
- **Dries to a protective film**
- **Corrosion inhibited**
- **Excellent adhesion**
- **Longer life of cables and chains**

## APPLICATION

PM322 Cable Guard may be applied by swabbing, dipping, and spraying. It can also be applied with drip oilers or force-fed applicators. Apply PM322 Cable Guard to lubricate and protect hemp cord, jute, sisal cord, wire cable, and chain.

## TYPICAL OBSERVATIONS

| | |
|---|---|
| Type | Asphaltic |
| Color | Black |
| Odor | Mild Hydrocarbon |
| Viscosity, ASTM D-1200 | |
| #4 Ford cup @ 77°F (25°F) | 15–17 sec |
| Density, lb/gal @ 77°F (25°C) | 7.00 |
| Specific Gravity @ 77°F (25°C) | 0.839 |
| Flash Point, ASTM D-93 | 105°F (40°C) |
| Dry Time, ASTM 5895 | 10–15 min |
| VOC, lb/gal | 3.89 |
| Shelf Life (unopened container) | Two years |

## RELATED PRODUCTS

1030 Water Soluble Corrosion Inhibitor Concentrate for Cables
1031 Water Soluble Corrosion Inhibitor Concentrate for Cables
759 Cable Guard Grease
773 Cable Coating
783 Biodegradable Marine Cable Coating
PM322M Cable Guard Chain and Cable Lubricant with Liquid Moly

© 2021, BALMAR LLC Made in U.S.A.

**WARRANTY** Because the conditions of use and the supervision of application are beyond our control, we assume no liability for any product failure or other damage beyond the purchase price of the material furnished by us. No agent, representative, or employee of this Company is authorized to change this provision, which relates to all goods delivered, whether sold, delivered as samples, or otherwise. Each user should independently determine the suitability of this product based on their specific application.

*Manufactured by*
**BALMAR LLC**
616 WEST PONT DES MOUTON ROAD | LAFAYETTE, LA 70507
Sales Locations:
LAFAYETTE, LA | HOUSTON, TX | LONGVIEW, TX | MIDLAND, TX | OKLAHOMA CITY, OK

*Registered trade name of Oil Center Research, Inc.
The product information and specifications listed in this publication are constantly being updated to keep up with government regulations and technology changes. Please visit our web site, www.oilcenter.com, or contact your Account Representative for the most current information relating to this product.