



Liquid-O-Ring®*

YOUR SUPER CENTER FOR OVER 1,000 TOP PERFORMANCE PRODUCTS SERVING INDUSTRIES WORLDWIDE

WWW.OILCENTER.COM

PM4000

TRANSMISSION GUARD

Automatic Hydraulic Transmission Fluid

- GEAR OILS
- MOTOR OILS
- HYDRAULIC OILS
- PIPE COATINGS
- THREAD SEALANTS
- BEARING GREASES
- SPECIALTY GREASES
- THREAD COMPOUNDS
- SUCKER ROD COATINGS
- OUTSIDE PRESERVATIVES
- WIRELINE GREASE SEALS
- CLEANERS & DEGREASERS
- PIPE STORAGE COMPOUNDS
- RUST & CORROSION INHIBITORS
- THREAD LOCKING COMPOUNDS
- VALVE LUBRICANTS & SEALANTS
- TOOL JOINT & DRILL COLLAR COMPOUNDS

PRODUCT DESCRIPTION

PM4000 Transmission Guard is a formulated using high quality oils and an additive package to meet the performance demands and extended drain intervals of modern automatic transmissions. Designed to provide complete protection to automatic transmission parts, PM4000 Transmission Guard offers excellent protection against corrosion, wear, and rust. It is oxidation resistant, and conditions oil seals. In addition, PM4000 Transmission Guard resists breakdown at high temperatures, thus reducing downtime for servicing. Its high viscosity index characteristics permit use of PM4000 Transmission Guard over a wide temperature range.

BENEFITS

- Meets the demands of modern automatic transmissions
- Protects against corrosion, wear, and rust
- Anti-foaming
- Oxidation stability
- Resists breakdown
- Wide temperature range
- Reduces friction
- Lower temperature fluidity for good cold start shifting
- Minimizes sludge and varnish deposits
- Smooth shifting

TYPICAL OBSERVATIONS

Color	Red
Odor	Mild
Density, lb/gal @ 77°F (25°C)	7.54
Specific Gravity	0.903
Flash Point, ASTM D-92	400°F (204°C)
Viscosity, @ 40°C cSt	40
Viscosity Index	190
Pour Point, ASTM D-97	-50°F (-45°C)

APPLICATION

PM4000 Transmission Guard meets the requirements as a GM Dexron® III Fluid, Mercon® Fluid, Caterpillar TO-2, and Allison C-4 fluid. PM4000 Transmission Guard meets requirements of Ford specification M2C33-F. PM4000 Transmission Guard is unsurpassed for quality and performance in ATF and hydraulic applications.



© 2012, BALMAR LLC Made in U.S.A.

WARRANTY Because the conditions of use and the supervision of application are beyond our control, we assume no liability for any product failure or other damage beyond the purchase price of the material furnished by us. No agent, representative, or employee of this Company is authorized to change this provision, which relates to all goods delivered, whether sold, delivered as samples, or otherwise. Each user should independently determine the suitability of this product based on their specific application.

Manufactured by

BALMAR LLC

616 WEST PONT DES MOUTON ROAD | LAFAYETTE, LA 70507

Sales Locations:

LAFAYETTE, LA | HOUSTON, TX | LONGVIEW, TX | MIDLAND, TX | OKLAHOMA CITY, OK

*Registered trade name of Oil Center Research, Inc. 10/01/13

The product information and specifications listed in this publication are constantly being updated to keep up with government regulations and technology changes. Please visit our web site, www.oilcenter.com, or contact your Account Representative for the most current information relating to this product.